

DTC UNSHIELDED PATCHPANEL LOADED CAT 6A – 24 PORT



DESCRIPTION

- Cat6A patch panel which is fully equipped with 24 unshielded keystone jacks and designed as jack ,wiring-free style satisfies or even exceeds current CAT 6A standard; guarantees 500MHZ broadband transmission, long-term reliability and stability; suitable for connection between workspace and Equipment room.

FEATURE & BENEFIT

- Design to mount to any standard 19" rack or cabinet
- 24 -port Cat 6A unshielded Patch panel
- Space saving, high-density 1U
- Black Electrostatic Powder-Coated Steel : phosphor bronze with tin plating over nickel . Meet or exceed the requirement of ANSI /TIA/EIA 568B.2
- Use keystone jacks and keystone inserts to configure your panel to accommodate a variety of schemes
- Sturdy Aluminum Plate around RJ 45 Jacks
- Phosphor bronze with 6-50 micro inches gold plated
- Available with T568 A, T568 B wiring pattern and meeting the requirement of Cat 6A standard
- Color Coded TIA/EIA 568A (international) and 568B (AT&T Standard) Wiring For Easy Installation
- Termination accepts 22,24& 26 AWG (0.64 ,0.5 and 0.4) solid wires
- Metal sheet : Corrosion resistant steel
- Plastic: fire self -extinguish high impact plastic

ELECTRICAL CHARACTERISTIC

- Dielectric Strength : 1000 V RMS 60 MHz / 1 min
- Rated current : Maximum 1.5 A
- Insulation Resistance (min) : 500 megaohm
- Contact Resistance (max) : 100 milliohm

